

Pergo Lofoten

Pergo parquet Lofoten, has following specifications:

- The parquet floor covering consists of panels of:
 - o 1820 x 190 x 12,5 mm.
- The floor covering must contain the following:
 - o HDF Mastercore
 - o Toplayer is Oak and 2,5 mm thickness
 - o Finishing can be UV cured water based lacquer (7 layers)
 - o Spruce or Pine backinglayer of 1,35 mm thickness
- The parquet floor covering is PEFC and Nordic Ecolabel (Nordic Swan) certified.
- EPD's are available on request.
- The slipperiness is minimum class USRV 50-52 according to CEN/TS 15676.
- The flooring panels have a formaldehyde emission class E1. The flooring is class A+ (very low VOC emission) for the indoor air quality. Parquet floor covering, with CE mark according to EN 14342:2008.
- The fire resistance class of the parquet floor covering, including the underlay prescribed by the manufacturer, is C_{fl}-s1 according to EN 13501-1.
- The parquet floor covering must correspond minimum to a falling sand test with a score of 500-1700 according to SIS 923509.
- The parquet floor benefits a lifetime warranty for residential use. For commercial application upon request.
- Thermal resistance of the parquet floor is 0.121 m²K/W.
- Installation can be done:
 - o Floatingly
 - o Glued
 - o Connection on short side can be done in 3 ways:
 - Fold down
 - Snapping
 - Rotating
 - o Unlimited possibility to uplift and RE-install has to be allowed without any quality loss
- Expansion gaps will be covered by wallbases or profiles with matching decors.
- Décor can be chosen in the collection Lofoten.